

GUARANTEED COMFORT

Fujitsu's heat pumps are designed to last and deliver unmatched performance year after year... This is why Fujitsu offers the only complete warranty on parts, labor and compressor. Do not be fooled by the warranties offered by other manufacturers. Furthermore, your Fujitsu certified dealer supported by The Master Group, the largest independent HVAC-R distributor in Canada. For 65 years, The Master Group has distinguished itself for its extensive inventory, exceptional customer service and technical expertise. An additional insurance for peace of mind for many years.

	9RL2		12RL2		18RLB ☆		24RLB		30RLXB		36RLXB	
Nominal cooling BTU/h	9,000		12,000		18,000		24,000		30,000		33,000	
Min. - max. cooling BTU/h	1,700-10,700		3,100-12,500		3,100-19,000		3,100-25,000		9,900-32,400		9,900-34,100	
Nominal heating BTU/h	10,000		14,000		18,000		24,000		30,000		34,000	
Min. - max. heating BTU/h	1,700-12,000		3,100-16,000		7,000-20,000		7,500-27,000		8,000-33,000		10,200-35,000	
SEER BTU/hW	16.0		16.0		19.0		18.0		16.5		15.5	
HSPF BTU/hW	9.0		9.0		10.6		10.6		9.0		9.0	
EER clg/htg	10.8/13.0		10.0/11.5		12.5		10.0		9.5		8.5	
Cooling operating range °F (°C)	14~115 (-10~46)		14~115 (-10~46)		14~115 (-10~46)		14~115 (-10~46)		14~115 (-10~46)		14~115 (-10~46)	
Heating operating range °F (°C)	14~75 (-10~24)		14~75 (-10~24)		5~75 (-15~24)		5~75 (-15~24)		5~75 (-15~24)		5~75 (-15~24)	
Moisture removal pt./h (l/h)	2.7 (1.3)		3.8 (1.8)		4.0 (1.9)		6.3 (3.0)		9.7 (4.6)		10.1 (4.8)	
Voltage/frequency/phase	115/60/1		115/60/1		208-230/60/1		208-230/60/1		208-230/60/1		208-230/60/1	
Max. current breaker (A)	15		20		15		20		30		30	
Air circ. C.F.M. (m ³ /h):	436 (740)		436 (740)		542 (920)		659 (1,120) clg 647 (1,100) htg		659 (1,120) clg 677 (1,150) htg		695 (1,180)	
Medium	353 (600)		353 (600)		439 (740)		530 (900)		530 (900)		530 (900)	
Low	265 (450)		265 (450)		365 (620)		436 (740)		436 (740)		436 (740)	
Quiet	191 (325)		191 (325)		306 (520)		365 (620)		365 (620)		365 (620)	
Noise level clg/htg dB(A) : Hi	43/43		43/43		42 / 43		47 / 47		47/49		50/50	
Medium	38/38		38/38		35 / 36		41 / 42		42/42		42/42	
Low	33/33		33/33		31 / 33		35 / 36		37/37		37/37	
Quiet	23/23		23/23		26 / 28		31 / 33		32/33		32/33	
Outdoor noise level clg/htg dB (A)	47/48		51/51		51 / 50		54 / 55		52/55		52/55	
Outdoor fan speed clg/htg RPM	-		-		870 / 780		1050 / 1000		850/850		850/850	
Fan speeds, stage	4 + auto		4 + auto		4 + auto		4 + auto		4 + auto		4 + auto	
Current rated cooling (A)	7.5		10.9		6.4 / 8.3		10.5 / 11.8		13.8/16.8		17.0/18.0	
Current rated heating (A)	7.0		11.0		5.8 / 11.8		8.5 / 13.8		12.3/18.8		14.8/18.8	
Power use rated clg (kW)	0.83		1.20		1.44 / 1.89		2.40 / 2.69		3.16/3.83		3.88/4.10	
Power use rated htg (kW)	0.77		1.21		1.29 / 2.69		1.93 / 3.14		2.80/4.28		3.39/4.28	
Air direction : Horizontal	manual		manual		auto		auto		auto		auto	
Vertical	auto		auto		auto		auto		auto		auto	
Air filter	washable		washable		washable		washable		washable		washable	
Connection method	flare		flare		flare		flare		flare		flare	
Combined min. lgth ft (m)	10 (3)		10 (3)		10 (3)		10 (3)		16 (5)		16 (5)	
Combined max. lgth ft (m)	66 (20) (pre-charge 49')		66 (20) (pre-charge 49')		66 (20) (pre-charge 49')		66 (20) (pre-charge 49')		165 (50) (pre-charge: 66')		165 (50) (pre-charge: 66')	
Max. vertical diff. ft (m)	49 (15)		49 (15)		49 (15)		49 (15)		98 (30)		98 (30)	
Conn. pipe diameter in	suc. 3/8 dis. 1/4		suc. 3/8 dis. 1/4		suc. 1/2 dis. 1/4		suc. 1/2 dis. 1/4		suc.5/8 dis.3/8		suc.5/8 dis.3/8	
Net weight lbs (kg)	16 (7) 64 (29)		16 (7) 69 (31)		31 (14) 86 (39)		31 (14) 86 (39)		31 (14) 134 (61)		31 (14) 134 (61)	
Dimensions : Height in (mm)	10 5/16 (262) 21 1/4 (540)		10 5/16 (262) 21 1/4 (540)		12 5/8 (320) 24 7/16 (620)		12 5/8 (320) 24 7/16 (620)		12 5/8 (320) 32 11/16 (830)		12 5/8 (320) 32 11/16 (830)	
Width in (mm)	32 9/32 (820) 26 (660)		32 9/32 (820) 26 (660)		39 5/16 (998) 31 1/8 (790)		39 5/16 (998) 31 1/8 (790)		39 5/16 (998) 35 7/16 (900)		39 5/16 (998) 35 7/16 (900)	
Depth in (mm)	8 1/8 (206) 11 11/32 (290)		8 1/8 (206) 11 11/32 (290)		9 (228) 11 7/16 (290)		9 (228) 11 7/16 (290)		9 (228) 13 (330)		9 (228) 13 (330)	
	ASU9RL2 indoor	AOU9RL2 outdoor	ASU12RL2 indoor	AOU12RL2 outdoor	ASU18RLB indoor	AOU18RLB outdoor	ASU24RLB indoor	AOU24RLB outdoor	ASU30RLXB indoor	AOU30RLXB outdoor	ASU36RLXB indoor	AOU36RLXB outdoor



☆ ENERGY STAR models



The best complete warranty available on the market is offered on each residential Fujitsu systems. To accept this offer, the qualifying product must be registered online via contractors.fujitsugeneral.com/registration/dsp_step_one.cfm within 60 days of the installation date. Otherwise, the manufacturer's standard 5-year parts and 7-year compressor warranty applies, no labor.



Authorized dealer



Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your contractor for details or visit www.energystar.gov.

